



LAWN & GARDEN

MODEL N° 6413

OWNER'S MANUAL

COOPY

Keep this Product ID Number and use when contacting Customer Service:

IMPORTANT! PLEASE READ BEFORE BEGINNING ASSEMBLY

Dear Valued Customer,

We would like to congratulate you on your purchase of a Lifetime® Outdoor Storage Shed! We are confident that you have made the perfect choice and you will be very pleased with your new storage solution.

Lifetime® Outdoor Storage is part of the family of products created and manufactured by Lifetime® Products, Inc. Like all of our products, you can be assured that the quality of your Lifetime Outdoor Storage Shed is the best in the world! And, we back that quality up by offering the best warranty in the business – A 10-year warranty that fully covers the Shed!

All of our Sheds are built with the highest-quality steel and high-density polyethylene (HDPE) parts. The design and construction of our steel-reinforced double-Wall Panels is second to none. All of our exposed steel parts and gables are powder coated and we use high-density polyethylene plastic. What makes polyethylene so special? It has superior strength and durability, and, it won't crack or degrade outdoors.

So now that you know the quality you are getting in a Lifetime Outdoor Storage Shed, please take the time to READ THIS INSTRUCTION MANUAL!

We have taken great care in providing the best possible form of instructions to help you put your new Outdoor Storage Shed together. Before you get started, PLEASE read the following preparation tips to help you get started!

We can assure you, your construction experience will be a lot more enjoyable if you do!

PREPARATION TIPS:

- The first step is simple... RELAX! You have made a great purchase, but Rome was not built in a day. Plan to spend a good part of your weekend putting together your fine Outdoor Storage Shed. Our philosophy is, if it comes together quickly and easily, it surely will come apart quickly and easily! Your Lifetime® Outdoor Storage Shed will surely last a long, long time, if you are patient, and take all the time necessary to put it together as we have instructed.
- Grab a friend to join in on the fun! This is not a one-person endeavor. We have found that not only will things go smoother if you have two or more people participating in the construction of the Shed, but it will go quicker as well. So, the more the merrier!
- Make sure you have all the tools necessary for constructing your new Shed. There is a "Tools Required For This Assembly" list on page five of this Owner's Manual.
- The plastic pieces of your Shed may become damaged by over tightening the screws. To avoid this damage, we strongly recommend the use of a low-powered power screwdriver or a drill that has an adjustable clutch that is set on a low-torque setting. If neither is available, use a hand screwdriver. If a hand screwdriver is all you have, take several breaks... your wrist will need it!
- You will also need two small ladders (when it comes time to do the roof!).

IMPORTANT! PLEASE READ BEFORE BEGINNING ASSEMBLY

- Before beginning assembly, remove the Parts List from the center of this Owner's Manual and take an inventory of the parts included with your Outdoor Storage Shed. Also, read through the entire instruction manual. It's always a great practice to get a feel for the flow of the process and to familiarize yourself with the parts involved. But, try not to get ahead of yourself and start the process out of order.
- FOLLOW THE INSTRUCTIONS IN ORDER! Everything goes together in a certain order, and we have learned what that correct order should be. In our state-of-the-art research and testing facility, we have painstakingly created these instructions. The order of construction is there for a reason, and some parts simply will not fit if built out of order. Just follow along with the order in the instructions and everything will fit together and things will go very smooth.
- YOUR SHED MUST BE BUILT ON A LEVEL SURFACE! If the spot you have chosen to place your wonderful new Outdoor Storage Shed is not level, the Shed will not assemble correctly! We recommend a concrete patio, a wood platform or creating a pad with pea gravel. Your Shed is meant to last a lifetime, so provide the proper foundation for it before you start to build.
- Before you build it, make sure you are allowed to build it! Consult all building codes, as well as city and county ordinances, to ensure that you do not require a building permit to construct your Outdoor Storage Shed. Proper building permit documentation may be required in your neighborhood, and it would be quite unfortunate to learn this after your Outdoor Storage Shed is already built!

Now that you're ready to begin the construction of your wonderful new Outdoor Storage Shed, step back, take a deep breath, get yourself a large cold beverage and enjoy yourself. We guarantee that after spending the right amount of time in building your Shed, you will be able to enjoy it for years to come.

Thanks for choosing Lifetime©, and have fun!

ABOUT LIFETIME PRODUCTS, INC.

Lifetime Products, Inc., has applied innovation and cutting-edge technology in plastics and metals to create a family of affordable lifestyle products that feature superior strength and durability. The world's leading manufacturer of folding tables and chairs, Lifetime was founded in 1986 as the maker of portable basketball systems that revolutionized the industry with patented technology. With diverse offerings such as outdoor storage sheds and steel utility trailers, Lifetime continues to develop innovative products that outfit the way you live.

Lifetime makes the things you need for the lifestyle you want. By innovating products in and around the home, Lifetime simplifies your everyday life and enables you to get the most out of your free time.



REGISTER YOUR LIFETIME PRODUCT TODAY!

There are benefits to registering your Lifetime product. With our new online product registration form, it's fast and easy! Register with us at www.lifetime.com and enjoy these great benefits:

- Receive exclusive money-saving offers from BuyLifetime.com, our online store, as well as NEW product notifications and special closeout promotions!
- In the unlikely event of a product recall or safety modification, we will notify you.
- Registering your product guarantees you warranty service. If you do not register your product, your warranty rights will not be diminished. But you will need to provide a sales receipt to verify your product purchase date before warranty service will be provided.

LIFETIME'S PROMISE TO YOU:

Maintaining your privacy is our long-standing policy at Lifetime. And you can rest assured that Lifetime will not sell or provide your personal data to other third parties, or allow them to use your personal data for their own purposes.

We invite you to read our privacy policy at www.lifetime.com

REGISTER today!

****U.S. and Canada customers ONLY****

IF ASSISTANCE IS NEEDED,

DO NOT CONTACT THE STORE!

CALL OUR CUSTOMER SERVICE DEPARTMENT at 1 (800) 225-3865

HOURS: 7:00 a.m. to 5:00 p.m. Monday through Friday (Mountain Standard Time)

Call, or visit our Web site for Saturday hours

For customers outside the U.S. or Canada, please contact the store for assistance.



SAFETY INSTRUCTIONS



FAILURE TO FOLLOW THESE WARNINGS MAY RESULT IN SERIOUS INJURY OR PROPERTY DAMAGE AND WILL VOID WARRANTY.

To ensure safety, do not attempt to assemble this product without following the instructions carefully. Check entire box and inside all packing material for parts and/or additional instruction material. Before beginning assembly, read the instructions and identify parts using the hardware identifier and parts list in this document. Proper and complete assembly, use and supervision are essential to reduce the risk of accident or injury.

- Do not use or store hot objects such as grills, blowtorches, welding equipment, etc. near the product.
- If using a ladder during assembly, use extreme caution.
- Two capable adults are required for assembly. (It is also recommended that a third adult function as an instruction reader.)


Most injuries are caused by misuse and/or not following instructions. Use caution when using this product.

BEFORE BEGINNING ASSEMBLY



Keep the hardware bags and their contents separate. If any parts are missing, call our Customer Service Department.

Read the “Congratulations” letter on page 2-3. Identify and inventory all parts and hardware using the parts and hardware lists and identifiers in this document.



****Two adults required to complete assembly****
(+ one adult suggested as an instruction reader)

Only adults should set up the product. Do not allow children in the set-up area until assembly is complete.



TOOLS REQUIRED FOR ASSEMBLY

7/16"




(2)

3/8"




(1)

Adjustable



(1)

Rubber Mallet



(1)

Box Knife



(1)

Phillips Screwdriver



(1)

Plain Screwdriver



(1)

3/8" Masonry Bit



(1)

Level



(1)

2" x 4" x 8' Leveling Board




(1)

6' Ladder




(2)

Power Drill*



(1)

Work Light



(1)

Pliers




(1)

Flashlight



(1)

Hammer Drill*



(1)

Safety Glasses



(1 for each person)

*See “Screwdriver Notice” on page 7.

Refer to the following areas throughout the instructions to assist in the assembly process:


This area is located at the top, left-hand corner of the page and indicates which tools and hardware are needed to complete the assembly steps on a page.



TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



This area is located at the top, right-hand corner of the page and shows an image of the product with shaded parts indicating which section is being assembled.



This area is usually located in the bottom, left-hand corner of a step and indicates that special attention is needed to perform a particular part of a step.



Note:

These areas are usually located in the bottom, right-hand corner of a step and indicate that damage to the product or serious injury may occur if the caution or warning is not heeded.



CAUTION



WARNING

IMPORTANT NOTICES

Level Surface Notice:

Surface must be leveled before installation. We recommend building a level work space with a concrete or patio style surface. If the surface is not properly leveled, the Outdoor Shed will not assemble correctly. Proper surface leveling will save you time in the long run, so please do not ignore this step.

Building Code Notice:

Consult all local building codes, as well as city and county ordinances, to ensure that the construction of the Outdoor Shed does not require a building permit. Proper building permit documentation may be required in your neighborhood, and it would be unfortunate to learn this after constructing the Shed.

Screwdriver Notice:

You may use a #2 Phillips head screwdriver bit and a power screwdriver or drill, instead of a hand screwdriver. However, be aware that the plastic pieces of your Shed can be damaged by overtightening of screws. To avoid damage we strongly recommend the use of a low-powered power screwdriver or a drill that has an adjustable clutch that is set on a low torque setting. If neither is available, use a hand screwdriver. In any case use caution to avoid overtightening the screws.

Floor Puncture Notice:

Sharp objects may damage your floor. If resting sharp, heavy objects on your Shed floor, place a block of wood between the sharp object and floor.



CAUTION:

If more than six (6) inches of snow accumulate on the roof of the shed, carefully remove the snow to avoid possible roof collapse. While standing on the ground, remove the snow from the roof with a broom or snow shovel. Do not stand on the roof to remove snow.


PARTS LIST

ID	Description	Qty	ID	Description	Qty
SHED PARTS BOX			BEG RIGHT DOOR ASSEMBLY HARDWARE		
AGZ	Right Door	1	AIK	Right Door Handle	1
AGO	Left Door	1	ABV	1/4" x 2" Carriage Bolt	2
AGF	Entry Gable	1	ADB	3/8" x 1/2" Steel Spacer	2
AGH	Rear Gable 1	1	AAB	1/4" Centerlock Nut	2
AGI	Rear Gable 2	1	AHY	Latch Spring	1
BLD	Floor Panel	1	AHW	Latch Block	1
AFV	90" Shelf	1	AIO	Thumb Lever	1
AGQ	Roof Panel	2	ADW	#10 x 3/4" Pan-Head Screw	4
AFH	Truss Gutter Channel	2	AHX	Latch Cover Plate	1
AFG	Roof Truss Brace	1	AHV	Door Latch	1
AFM	Shelf Support Channel	2	AIL	Right Door Lock Bracket	1
AFC	Door End Channel	2	AEB	1/4" Flat Washer	2
AFE	Entry Header Bar	1	AEE	#10 x 1/2" Flat Washer	5
AGY	Corner Wall Panel 104	1	BHZ DOOR & FRONT GABLE INSTALLATION HARDWARE		
AGN	Corner Wall Panel 105	1	ADZ	1/4" x 5/8" Pan-Head Screw	6
AGW	Corner Wall Panel 106	1	AHO	Door Hinge Bushing	2
AGL	Corner Wall Panel 107	1	AHP	Cotter Pin	2
AHD	Wall Panel	2	AIC	Left Gap Flap	1
AHC	Skylight	1	AIM	Right Gap Flap	1
AGG	Front Roof Cap	1	ADX	#10 x 1/2" Pan-Head Screw	4
AFW	Rear Roof Cap	1	BRY REAR GABLE, ROOF, & TRUSS INSTALLATION HARDWARE		
AFZ	Corner Shelf	2	ADZ	1/4" x 5/8" Pan-Head Screw	48
AFS	10" x 30" Shelf	2	AED	#10-1" Fender Washer	6
BHV GABLE ASSEMBLY HARDWARE (x2)			ADX	#10 x 1/2" Pan-Head Screw	22
AGP	Louvered Vent	1	AXX	Truss Hole Insert	2
AIQ	Vent Screen	1	BHC PEGBOARD STRIP INSTALLATION HARDWARE		
ADW	#10 x 3/4" Pan-Head Screw	5	ADW	#10 x 3/4" Pan-Head Screws	10
AEE	#10 x 1/2" Flat Washer	5	BHD Tool Clip Assortment [1029336]		
ADZ	1/4" x 5/8" Pan-Head Screw	4	AIF	2" Double-Arm Hook	1
AHS	End Plug	2	AIG	4" Double-Arm Hook	1
ADV	1/4" x 1 1/8" Pan-Head Screw	6	AIH	J-Hook	3
ACB	#10 x 1 1/8" Pan-Head Screw	1	AIL	L-Hook	3
BRW SMALL PARTS BOX			AIJ	Toolholder	2
AIX	Wood Shim	4	SHELF HARDWARE		
AIW	Wood Block	1	BHH 90" Long Shelf Installation Hardware		
AYJ	Battery-Powered Light	1	ADZ	1/4" x 5/8" Pan-Head Screw	14
AFU	Pegboard Strip	1	AIY	Shelf Support Bracket	2
BDZ TOOL HARDWARE BAG			BLE Corner Shelf Installation Hardware (x2)		
ADC	#2 Phillips Bit	1	ADZ	1/4" x 5/8" Pan-Head Screw	4
BEA TRUSS FRAME ASSEMBLY HARDWARE			BHI 10" x 30" Shelf Installation Hardware (x2)		
ADJ	1/4" Cap Nut	2	ADZ	1/4" x 5/8" Pan-Head Screw	12
ADY	#10 x 3/8" Pan-Head Screw	6	AIY	Shelf Support Bracket	4
ADK	#10 Cap Nut	6	BHB BATTERY-POWERED LIGHT HARDWARE		
AIP	Truss Connector	1	ADZ	1/4" x 5/8" Pan-Head Screw	3
ADH	1/4" Threaded Rod	1			
BQF FLOOR & WALL ASSEMBLY HARDWARE					
ADZ	1/4" x 5/8" Pan-Head Screw	38			
BEF LEFT DOOR ASSEMBLY HARDWARE					
AHZ	Left Door Handle	1			
AHM	Deadbolt Latch	2			
ABU	1/4" x 1 1/2" Carriage Bolt	2			
ADW	#10 x 3/4" Pan-Head Screw	3			
AEE	#10 x 1/2" Flat Washer	3			
ADJ	1/4" Cap Nut	2			
AIA	Left Door Lock Bracket	1			
AIB	Left Door Strike Plate	1			


PARTS IDENTIFIER

SHED PARTS BOX


Parts shown at 4% scale




AGO (x1)
Left Door




AGZ (x1)
Right Door



AGF (x1)
Entry Gable




AGQ (x2)
Roof Panel



AGH (x1)
Rear Gable 1

AGI (x1)
Rear Gable 2



BLD (x1)
Floor Panel





AFV (x1)
90" Shelf



PARTS IDENTIFIER

SHED PARTS BOX



Parts shown at 8% scale




AFC (x2)
Door End Channel





AFH (x2)
Truss Gutter Channel



AFE (x1)
Entry Header Bar




AFG (x1)
Roof Truss Brace




AFM (x2)
Shelf Support Channel

Parts shown at 8% scale



AHC (x1)
Skylight




AFZ (x2)
Corner Shelf


PARTS IDENTIFIER

SHED PARTS BOX


Parts shown at 4% scale




AGY (x1)
Corner Wall Panel 104




AGN (x1)
Corner Wall Panel 105




AGW (x1)
Corner Wall Panel 106




AGL (x1)
Corner Wall Panel 107




AHD (x2)
Wall Panel



AGG (x1)
Front Roof Cap



AFW (x1)
Rear Roof Cap



1002314

AFS (x2)
10" x 30" Shelf

HARDWARE IDENTIFIER

SMALL PARTS BOX [BRW]


Parts are not shown to scale



AIW (x1)
Wood Block




AIX (x4)
Wood Shim



AYJ (x1)
Battery-Powered Light

Parts shown at 15% of actual size



AFU (x2)
Pegboard Strip

TOOL HARDWARE BAG [BDZ]

Tool shown at actual size




ADC (x1)
#2 Phillips Bit

TRUSS FRAME ASSEMBLY HARDWARE [BEA]

Hardware shown at actual size (*unless otherwise noted)




ADK (x6)
#10 Cap Nut




ADY (x6)
#10 x 3/8" Pan-Head Screw



ADJ (x2)
1/4" Cap Nut




***AIP** (x1)
Truss Connector



***ADH** (x1) 1/4" Threaded Rod

FLOOR & WALL ASSEMBLY HARDWARE [BQF]


Hardware shown at actual size




ADZ (x38)
1/4" x 5/8" Pan-Head Screw
(Not all screws will be used)

GABLE ASSEMBLY HARDWARE [BHV] x2

Parts shown at 8% scale




AGP (x1)
Louvered Vent




AIQ (x1)
Vent Screen


Hardware shown at actual size




ADZ (x4)
1/4" x 5/8" Pan-Head Screw
(Only 4 used)




AHS (x2)
End Plug
(Only 2 used)




AEE (x5)
#10 x 1/2"
Flat Washer



ADV (x6)
1/4" x 1 1/8" Pan-Head Screw
(Only 6 used)



ADW (x5)
#10 x 3/4" Pan-Head Screw




ACB (x1)
#10 x 1 1/8" Pan-Head Screw
(Not used in this model)

HARDWARE IDENTIFIER

LEFT DOOR ASSEMBLY HARDWARE [BEF]

Part shown at 15% scale : Parts shown at 25% scale




AHZ (x1)
Left Door Handle



AHM (x2)
Deadbolt Latch



AIA (x1)
Left Door Lock Bracket




AIB (x1)
Left Door Strike Plate


Hardware shown at actual size




ADJ (x2)
1/4" Cap Nut



ABU (x2)
1/4" x 1 1/2" Carriage Bolt




ADW (x3)
#10 x 3/4" Pan-Head Screw



AEE (x3)
#10 x 1/2" Flat Washer

RIGHT DOOR ASSEMBLY HARDWARE [BEG]


Part shown at 15% scale : Parts shown at 25% scale




AIK (x1)
Right Door Handle




AHX (x1)
Latch Cover Plate



AIL (x1)
Right Door Lock Bracket




AIO (x1)
Thumb Lever




AHV (x1)
Door Latch


Hardware shown at actual size



ADW (x4)
#10 x 3/4" Pan-Head Screw




ABV (x2)
1/4" x 2" Carriage Bolt



AEE (x5)
#10 x 1/2" Flat Washer
(Only 3 used)


Part shown at 50% scale




AHW (x1)
Latch Block




ADB (x2)
3/8" x 1/2" Steel Spacer



AEB (x2)
1/4" Flat Washer



AAB (x2)
1/4" Centerlock Nut




AHY (x1)
Latch Spring


HARDWARE IDENTIFIER

DOOR & FRONT GABLE INSTALLATION HARDWARE [BHZ]


Hardware shown at actual size (*unless otherwise noted)




ADZ (x6)
1/4" x 5/8" Pan-Head Screw



***AIC** (x1)
Left Gap Flap



***AIM** (x1)
Right Gap Flap



ADX (x4)
#10 x 1/2" Pan-Head Screw




AHO (x2)
Door Hinge Bushing




AHP (x2)
Cotter Pin

REAR GABLE, ROOF, & TRUSS INSTALLATION HARDWARE [BRY]


Hardware shown at actual size (*unless otherwise noted)




ADZ (x48)
1/4" x 5/8" Pan-Head Screw
(Not all screws will be used)



AED (x6)
#10 x 1" Fender Washer



***AXX** (x2)
Truss Hole Insert




ADX (x22)
#10 x 1/2" Pan-Head Screw

SHELF INSTALLATION HARDWARE

90" Long Shelf Installation Hardware [BHH]

Hardware shown at actual size



ADZ (x14)
1/4" x 5/8" Pan-Head Screw


Part shown 15% scale



AIY (x2)
Shelf Support Bracket

Corner Shelf Hardware [BLE] (x2)


Hardware shown at actual size



ADZ (x4)
1/4" x 5/8" Pan-Head Screw

10" x 30" Shelf Hardware [BHI] (x2)

Hardware shown at actual size



ADZ (x12)
1/4" x 5/8" Pan-Head Screw

Part shown 15% scale




AIY (x4)
Shelf Support Bracket

HARDWARE IDENTIFIER

PEGBOARD STRIP INSTALLATION HARDWARE [BHC]


Parts shown at actual size




ADW (x10)
#10 x 3/4" Pan-Head Screw

Tool Clip Assortment [BHD]


Parts shown at 50% of actual size



AIF (x1)
2" Double-Arm Hook




AIG (x1)
4" Double-Arm Hook



AII (x3)
L-Hook




AIJ (x2)
Toolholder



AIH (x3)
J-Hook

BATTERY-POWERED LIGHT HARDWARE [BHB]


Hardware shown at actual size



ADZ (x3)
1/4" x 5/8" Pan-Head Screw



TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



Concrete (1/3 cu. yd.)

SEC 1




SEC

1.1

SITE PREPARATION - CONCRETE PLATFORM PREPARATION

The actual dimensions of your shed (at its widest and longest points) are 8' x 2' 6". Ensure you select a site that will accommodate these measurements. The base of the shed is slightly smaller than this, so you will need to create a level surface that is at least 93 1/2" x 28 1/4". We recommend using a level cement or patio style surface. This will provide the best long-term performance for your shed.

! Note: Shed Extension Kits are available for this shed. Please consider possible shed expansion when planning the site for your shed. See back cover of this manual for information on ordering accessories.




! Note: Surface must be leveled before installation. If the surface is not properly leveled, the Outdoor Shed will not assemble or function correctly. Proper surface leveling will save you time in the long run, so please do not ignore this step.

! Note: Any platform or similar structure should be built above ground in order to avoid water pooling inside the Shed.




TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



2" x 4" x 28 1/4" (x2) (Not included)




2" x 4" x 90 1/2" (x3) (Not included)



16d 3" Common Nail (x12) (Not included)

SEC 1



SEC


1.2

ALTERNATIVE SITE PREPARATION: OPTION 1 - WOOD PLATFORM ASSEMBLY



Ensure all lumber used is treated and approved for outdoor use. Build outside frame to 93 1/2" x 28 1/4" **outside dimensions**:



Note: Whenever possible, you should use the surfaces described on Page 7. When this is not possible, we recommend you use a wood platform or a filled wood frame.



Outside Dimensions



Place the 2" x 4" x 28 1/4" boards on the outside of the frame. Nail each board in place with the 16d nails.




Note: All lumber must be rated for outdoor use.




Note: Surface must be leveled before installation. If the surface is not properly leveled, the Outdoor Shed will not assemble or function correctly. Proper surface leveling will save you time in the long run, so please do not ignore this step.



TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



28 1/4" x 93 1/2" x 3/4" Treated Plywood (x1) (Not included)



8d 1 1/2" Common Nail (x22)
(Not included)

SEC 1




SEC

1.3

ALTERNATIVE SITE PREPARATION: OPTION 1 - WOOD PLATFORM ASSEMBLY (CONT)

Square up the frame by measuring from corner to corner. Measurement A should equal Measurement B.




Note: All lumber must be rated for outdoor use.

SEC

1.4

Cut Plywood to the required size. Arrange the Plywood according to the diagram and nail into place with 8d x 1 1/2" nails. Place platform in the desired location. If platform does not rest level on the ground, build up low points with loose dirt until platform is stable. Drill three evenly spaced 1/2" drain holes in plywood between each 2" x 4" joist.




Drill three evenly spaced 1/2" drain holes in plywood between each 2" x 4" joist.




TOOLS AND HARDWARE REQUIRED FOR THIS PAGE

2" x 4" x 96" (x2) (Not included)




2" x 6" x 23" (x2) (Not included)




8d 1 1/2" Common Nail (x16)
(Not included)



Pea Gravel (4.5 Cubic Feet)
(Not included)



L-Bracket (x4)
(Not included)



SEC 1

SEC

1.5

ALTERNATIVE SITE PREPARATION: OPTION 2 - FILLED WOOD FRAME ASSEMBLY



Cut outside frame to 8' x 2'6" outside dimensions. Lay boards flat so widest parts face up. Ensure frame is level. Square up the frame by measuring from corner to corner. Measurement A should equal Measurement B. Nail an L-Bracket on each corner of the frame with 8d nails. Place platform in the desired location. If platform does not rest level on the ground, build up low points with loose dirt or "Pea" gravel, until platform is stable.



Note: Whenever possible you should use the surfaces described on Page 7.




Note: All lumber must be rated for outdoor use.



SEC

1.6


Once all boards are level and do not wobble, pack "Pea" gravel around the outside of the frame, and slope away from frame.



SEC

1.7

Now fill the inside of the frame with "Pea" gravel. Use a leveling board to scrape off extra fill material and to level the surface.




2" x 4" x 2'6" Leveling Board (x1)


SEC 2 FLOOR & WALL ASSEMBLY

HARDWARE REQUIRED

Hardware shown at actual size



ADZ (x38)
1/4" x 5/8" Pan-Head Screw
(Not all are used)



AHO (x2)
Door Hinge Bushing


Remove the two (2) Door Hinge Bushings (AHO) from Door & Entry Gable Installation Hardware Bag.

METAL PARTS REQUIRED


NO METAL PARTS REQUIRED FOR THIS SECTION

PLASTIC PARTS REQUIRED


Parts shown at 4% of actual size




AGY (x1)
Corner Wall Panel 104




AGN (x1)
Corner Wall Panel 105




AGW (x1)
Corner Wall Panel 106



AGL (x1)
Corner Wall Panel 107




BLD (x1)
Floor Panel




AHD (x2)
Wall Panel

TOOLS REQUIRED



Phillips Screwdriver



Safety Glasses



AIW (x1)
Wood Block




TOOLS AND HARDWARE REQUIRED FOR THIS PAGE


SEC 2



AIW (x1)
Wood Block



AHO (x2)




SEC

2.1

FLOOR ASSEMBLY

Lay the **Floor Panel (BLD)** flat on the ground. Remove the two (2) **Door Hinge Bushings (AHO)** from the **Door & Entry Gable Installation Hardware Bag**. Lift the Floor Panel up enough to slide the Door Hinge Bushings under and up through the holes in the Floor Panels as shown. This will be the front of your shed. The door hinges will be inserted in these bushings later in the assembly.



CAUTION


Sharp objects may damage your floor. If resting sharp, heavy objects on your shed floor, place a block of wood between the sharp object and floor.

SEC

2.2

WALL ASSEMBLY



Fold **Corner Wall Panel 105 (AGN)**. Fit tabs of Panel into the front left corner (while facing shed) of your floor. Place the **Wood Block (AIW)** under directly under the first tab of the Floor Panel, then pull down on Corner Panel until tab snaps into place. Move Wood Block under the next tab and repeat.



! Note: Place Wood Block (AIW) directly under the tab you are inserting. Snap tabs into place one at a time.



TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



AIW (x1)
Wood Block





SEC 2



SEC

2.3


Fit tabs of the **Corner Wall Panel 107 (AGL)** into the back left corner of your floor.



SEC

2.4



Fasten Corner Panels together using the required hardware.



Note: Second person should apply pressure on opposite side of the wall for easy insertion of screws.




TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



AIW (x1)
Wood Block




SEC 2



SEC

2.5


Snap **Wall Panels (AHD)** into place along the rear side of the Floor Panel, and fasten together using the required hardware.



SEC



2.6

Snap the tabs of the **Corner Wall Panel 106 (AGW)** into position, as shown. Secure the Panels using the required hardware.






TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



AIW (x1)
Wood Block




SEC 2



SEC


2.7

Fit tabs of the **Corner Wall Panel 104 (AGY)** into position, as shown. Secure the Panels using the required hardware.






TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



IF YOU PLAN ON ANCHORING YOUR SHED, CHECK WITH YOUR LOCAL HARDWARE STORE FOR SUITABLE HARDWARE.

SEC 2




SEC

2.8

ANCHORING THE SHED

If you plan on anchoring your shed, you can anchor it to your platform through the four indentations near the corners of the floor. The anchoring hardware used depends on the platform. If you have a concrete platform, we recommend using four (4) 3/8" Anchor Bolts and four (4) 3/8" x 1" Flat Washers. If you have a wood framed platform, we recommend using four (4) 3/8" Lag Bolts and four (4) 3/8" x 1" Flat Washers. Do not exceed a 3/8" diameter bolt. Refer to your local hardware store for this hardware. **Do not tighten anchoring hardware until instructed to do so at the end of these instructions.**




WARNING

Failure to anchor the shed may result in property damage and/or personal injury.

SEC 3 TRUSS ASSEMBLY

HARDWARE REQUIRED

Hardware shown at actual size



ADY (x6)
#10 x 3/8" Screw




ADJ (x2)
1/4" Cap Nut




ADK (x6)
#10 Cap Nut

METAL PARTS REQUIRED



Parts shown at 8% of actual size (*Unless indicated otherwise)



AFH (x2)
Truss Gutter Channel




AFG (x1)
Roof Truss Brace (Not to Scale)



***AIP (x1)**
Truss Connector

Part shown at 50% of actual size




ADH (x1) 1/4" Threaded Rod

PLASTIC PARTS REQUIRED

NO PLASTIC PARTS REQUIRED FOR THIS SECTION

TOOLS REQUIRED




Phillips Screwdriver



7/16" Wrench




3/8" Wrench




Safety Glasses



TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



3/8"



ADY (x1)



ADK (x1)

SEC 3




NOTE: YOU NEED ONLY COMPLETE THIS STEP IF THIS SHED IS FOR A DISPLAY MODEL ONLY

SEC

3.1


TRUSS ASSEMBLY

Stand a **Truss Gutter Channel (AFH)** upright and set a **Truss Connector (AIP)** inside the end of the Channel as shown. Align the holes and secure with one (1) #10 x 3/8" **Pan-Head Screw (ADY)** and one (1) #10 **Cap Nut (ADK)**.






TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



3/8"



ADY (x1)



ADK (x1)


SEC. 3



SEC


3.2

Connect another **Truss Gutter Channel (AFH)** to the Truss Connector using one (1) **#10 x 3/8" Pan-Head Screw (ADY)** and one (1) **#10 Cap Nut (ADK)**.






TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



3/8"



ADY (x4)



ADK (x4)


SEC 3



SEC

3.3


Lay the Truss Assembly on its side, and align the holes in a **Roof Truss Brace (AFG)** with those circled on the Truss Gutter Channels as shown.



SEC

3.4

Secure the Roof Truss Brace to the Truss Gutter Channel using two (2) **#10 x 3/8" Pan-Head Screws (ADY)** and two (2) **#10 Cap Nuts (ADK)**. Repeat this step for the other end of the Roof Truss Brace.



Note: The Cap Nuts goes on the outside of the Truss.



WARNING

Do not overtighten the Cap Nut. If the end of the Bolt breaks through the plastic cap, call our Customer Service Department. Exposed threads on the end of the Bolt may cause serious injuries.




TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



7/16" (x2)





ADJ (x2)



SEC

3.5

With the Truss Assembly on its side, slide a **1/4" Threaded Rod (ADH)** through the Roof Truss Brace and Truss Connector as shown. Secure the top and bottom of the 1/4" Threaded Rod with a **1/4" Cap Nut (ADJ)**. Tighten all hardware. The 1/4" Threaded Rod will still spin freely. Set aside.




WARNING

Do not overtighten the Cap Nut.


SEC 4 LEFT DOOR ASSEMBLY

HARDWARE REQUIRED

Hardware shown at actual size




ADW (x3)
#10 x 3/4" Pan-Head Screw



ABU (x2)
1/4" x 1 1/2" Carriage Bolt




ADJ (x2)
1/4" Cap Nut




AEE (x3)
#10 x 1/2" Flat Washer

Part shown at 25% of actual size



AHM (x2)
Deadbolt Latch



AIB (x1)
Left Door Strike Plate



AIA (x1)
Left Door Lock Bracket


Part shown at 15% of actual size




AHZ (x1)
Left Door Handle

METAL PARTS REQUIRED

Part shown at 8% of actual size




AFC (x1)
Door End Channel



PLASTIC PARTS REQUIRED

Part shown at 4% of actual size



AGO (x1)
Left Door


TOOLS REQUIRED



Phillips Screwdriver




7/16" Wrench



Safety Glasses



TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



AHM (x2)

SEC 4




SEC

LEFT DOOR ASSEMBLY

4.1

Rest **Left Door (AGO)** with front side down. Position **Deadbolt Latches (AHM)** in slots at top and bottom of Door then slide **Door End Channel (AFC)** onto the Door.



! Note: The Door End Channel fits onto Door with the flat side up (facing the Deadbolt Latches).




TOOLS AND HARDWARE REQUIRED FOR THIS PAGE


SEC 4




7/16"




AIB (x1)



ABU (x2)



ADJ (x2)




AIA (x1)



SEC

4.2

Slip the **Left Door Strike Plate (AIB)** over the Left Shed Door and align the holes.




AIB

! Note: You may need to nudge the Door End Channel to make these holes line up with the gap in the Door.

SEC

4.3

Attach the **Left Door Lock Bracket (AIA)** to the Left Door Strike Plate with two **1/4" x 1 1/2" Carriage Bolts (ABU)** and two **1/4" Cap Nuts (ADJ)**.



AIA

ABU






WARNING

Do not overtighten the Cap Nut. If the end of the Bolt breaks through the plastic cap, call our Customer Service Department. Exposed threads on the end of the Bolt may cause serious injuries.




TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



SEC

4.4


Attach the **Left Door Handle (AHZ)** using three (3) #10 x 1/2" Flat Washers (AEE) and three (3) #10 x 3/4" Pan-Head Screws (ADW).




SEC 5 RIGHT DOOR ASSEMBLY

HARDWARE REQUIRED

Hardware shown at actual size




ABV (x2)
1/4" x 2" Carriage Bolt




AEE (x5)
#10 x 1/2 Flat Washer
(Only 3 are used)




ADB (x2)
3/8" x 1/2" Steel Spacer




AAB (x2)
1/4" Centerlock Nut



AHY (x1)
Latch Spring




ADW (x4)
#10 x 3/4" Pan-Head Screw




AEB (x2)
1/4" Flat Washer


Part shown at 25% of actual size




AHX (x1)
Latch Cover Plate



AIL (x1)
Right Door Lock Bracket



AIO (x1)
Thumb Lever




AHV (x1)
Door Latch

Part shown at 15% of actual size



AIK (x1)
Right Door Handle

Part shown at 50% of actual size




AHW (x1)
Latch Block

METAL PARTS REQUIRED

Part shown at 8% of actual size




AFC (x1)
Door End Channel




PLASTIC PARTS REQUIRED

Part shown at 4% of actual size



AGZ (x1)
Right Door

TOOLS REQUIRED



Phillips Screwdriver




7/16" Wrench



Safety Glasses



TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



NO HARDWARE REQUIRED FOR THIS PAGE

SEC. 5




SEC

RIGHT DOOR ASSEMBLY


5.1

Rest **Right Door (AGZ)** with front side down, then slide **Door End Channel (AFC)** onto the Door.





TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



NO HARDWARE REQUIRED FOR THIS PAGE


SEC 5



SEC

5.2


Fit knobs of **Thumb Lever (A10)** into the grooves of **Right Door Handle (A1K)**.



SEC


5.3

Rotate the Thumb Lever into the Right Door Handle. Slide forward until the knobs fit into the holes in the Handle.







TOOLS AND HARDWARE REQUIRED FOR THIS PAGE




7/16"




ABV (x2)




ADW (x3)




AAB (x2)



ADB (x2)



AEB (x2)



AEE (x3)


SEC. 5



SEC

5.4

Attach the Right Handle Assembly to the Door using three (3) #10 x 1/2" Flat Washers (AEE) and three (3) #10 x 3/4" Pan-Head Screws (ADW).





CAUTION

Do not overtighten. Overtightening may damage parts and void warranty.

SEC

5.5

Install Handle Latch assembly onto the Right Shed Door using the required hardware.





Note: The Door Latch (AHV) goes on top of the Thumb Lever (AIO).




TOOLS AND HARDWARE REQUIRED FOR THIS PAGE


SEC 5



AHY (x1)



AHW (x1)




ADW (x1)



SEC

5.6

Line up the hole in the **Latch Block (AHW)** with the hole in the Thumb Lever and secure with one (1) **#10 X 3/4" Pan-Head Screw (ADW)**.




Note: The lip of the Latch Block (AHW) fits under the Thumb Lever (A10).

SEC

5.7

Attach **Latch Spring (AHY)** to the **Door Latch (AHV)** and the **Latch Cover Plate (AHX)**. Set the Door aside.



Note: Use pliers to pull spring down and hook into bottom hole.



WARNING




When pulling on spring, each person should use protective eye glasses to help prevent serious eye injury.


SEC 6 GABLE ASSEMBLY

HARDWARE REQUIRED


Hardware shown at actual size




AEE (x10)
#10 x 1/2" Flat Washer




ADW (x10)
#10 x 3/4" Pan-Head Screw




ADZ (x8)
1/4" x 5/8" Pan-Head Screw
(Only 4 used)



ADV (x12)
1/4" x 1 1/8" Pan-Head Screw
(Only 6 used)




AHS (x4)
End Plug
(Only 2 used)




ACB (x2)
#10 x 1 1/4" Pan-Head Screw
(Not used in this model)

METAL PARTS REQUIRED

Part shown at 8% of actual size




AFE (x1)
Entry Header Bar




PLASTIC PARTS REQUIRED

Parts shown at 4% of actual size




AGF (x1)
Entry Gable

(Rear View)



AGH (x1)
Rear Gable 1


(Rear View)




AGI (x1)
Rear Gable 2

(Rear View)

Parts shown at 8% of actual size




AGP (x2)
Louvered Vent




AIQ (x2)
Vent Screen

TOOLS REQUIRED





Phillips Screwdriver



Safety Glasses



TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



ADZ (x4)

SEC. 6




SEC

REAR GABLE ASSEMBLY

6.1


Lay the edge of **Rear Gable 2 (AGI)** over **Rear Gable 1 (AGH)** as shown, and align the four holes.



SEC

6.2



Connect Rear Gables 1 & 2 together using four (4) **1/4" x 5/8" Pan-Head Screws (ADZ)** as shown.




Note: Only use a hand screwdriver in this step.



TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



ADW (x5)



AEE (x5)


SEC 6



SEC

6.3


Lay Rear Gable Assembly flat on the ground over the **Vent Screen (AIQ)** and **Louvered Vent (AGP)**. Align the holes in the Louvered Vent with those in the Rear Gable Assembly.



SEC

6.4



After aligning the holes, press down firmly on the Rear Gable Assembly while inserting the five (5) **#10 x 3/4" Pan-Head Screws (ADW)** and the five (5) **#10 x 1/2" Flat Washers (AEE)**. Pressing down firmly while inserting the Screws will help prevent the Vent Screen from twisting. Set aside.




Note: Only use a hand screwdriver in this step.



TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



ADW (x5)



AEE (x5)

SEC. 6




SEC

ENTRY GABLE ASSEMBLY

6.5


Lay **Entry Gable (AGF)** flat on the ground over the **Vent Screen (AIQ)** and **Louvered Vent (AGP)** as shown. Align the holes in the Louvered Vent with those in the Entry Gable.



SEC

6.6


After aligning the holes, press down firmly on the Entry Gable when inserting the five (5) **#10 x 3/4" Pan-Head Screws (ADW)** and the five (5) **#10 x 1/2" Flat Washers (AEE)**. Pressing down firmly while inserting the Screws will help prevent the Vent Screen from twisting.



Note: Only use a hand screwdriver in this step.



TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



AHS (x2)



ADV (x6)




SEC 6

SEC

6.7

Insert an **End Plug (AHS)** into each end of **Entry Header Bar (AFE)**.




Note: Only use a hand screwdriver in this step.

SEC

6.8

Attach the Entry Header Bar to the Entry Gable Assembly, and secure with six (6) **1/4" x 1/8" Pan-Head Screws (ADV)**. Set aside.




Note: Only use a hand screwdriver in this step.

SEC 7 DOOR & ENTRY GABLE INSTALLATION

HARDWARE REQUIRED


Hardware shown at actual size (*Unless noted otherwise)




ADZ (x6)
1/4" x 5/8" Pan-Head Screw




AHP (x2)
Cotter Pin



ADX (x4)
#10 x 1/2" Pan-Head Screw



***AIM (x1)**
Right Gap Flap




***AIC (x1)**
Left Gap Flap

METAL PARTS REQUIRED

NO METAL PARTS REQUIRED FOR THIS SECTION


PLASTIC PARTS REQUIRED

Parts shown at 4% of actual size




Entry Gable Assembly

Rear View




Left Door Assembly




Right Door Assembly

TOOLS REQUIRED



Phillips Screwdriver




Pliers



Safety Glasses




TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



AHP (x2)

SEC 7




SEC

DOOR INSTALLATION

7.1




Align the hole in the bottom of the Hinge of the **Left Door Assembly** with the hole in the Door Hinge Bushing on the Floor of your shed, and insert the Door Hinge Tube into the Door Hinge Bushing.



SEC

7.2

Insert a **Cotter Pin (AHP)** through the Bushing and Door Hinge. Use a pair of pliers to bend the ends of the Cotter Pins outward. **Repeat these steps for the Right Door Assembly.**




Note: Use pliers to bend back the ends of the Cotter Pin (AHP).



Note: Ensure that these two holes line up, so that the Cotter Pin (AHP) can be inserted.



TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



SEC 7




2 ADULTS REQUIRED FOR THESE STEPS

SEC

FRONT GABLE INSTALLATION

7.3



Slide the two holes in the **Entry Gable Assembly** down over the Door Hinge Tubes as shown.



SEC



7.4

Align the holes in the sides of the Entry Gable Assembly with those in the tops of the Corner Wall Panels and secure with six (6) **1/4" x 5/8" Pan Head Screws (ADZ)** at the locations indicated.







TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



ADX (x4)




AIM (x1)
(Not to scale)



AIC (x1)
(Not to scale)

SEC 7






SEC

7.5

GAP FLAP INSTALLATION


Attach the **Right & Left Gap Flaps (AIM & AIC)** to the top, right and left corners of the Side Doors as shown. Before completely tightening the **#10 x 1/2" Pan-Head Screws (ADX)**, slide the Gap Flaps up until they cover any gap between the tops of the Doors and the Gable.




SEC 8 REAR GABLE, ROOF, & TRUSS INSTALLATION

HARDWARE REQUIRED


Hardware shown at actual size (*Unless otherwise noted)




ADZ (x48)
1/4" x 5/8" Pan-Head Screw
(Not all screws will be used)



ADX (x22)
#10 x 1/2" Pan-Head Screw
(Only 6 used)




AED (x6)
#10 x 1" Fender Washer



***AXX (x2)**
Truss Hole Insert

METAL PARTS REQUIRED

Parts shown at 8% of actual size




Truss Frame Assembly

PLASTIC PARTS REQUIRED


Parts shown at 4% of actual size

115




AGG (x1)
Front Roof Cap

116




AFW (x1)
Rear Roof Cap




AGQ (x2)
Roof Panel

Part shown at 8% of actual size



AHC (x1)
Skylight




Conjunto del faldón trasero


TOOLS REQUIRED



Phillips Screwdriver




Flashlight




Safety Glasses




TOOLS AND HARDWARE REQUIRED FOR THIS PAGE

**SEC 8****SEC****8.1**

Attach the Rear Gable Assembly to the shed as shown and secure with fourteen (14) 1/4" x 5/8" Pan-Head Screws (ADZ).



**SEC****8.2**

Set a **Roof Panel (AGQ)** onto the two Gable Assemblies. The Gables fit into the grooves along the underside of the Roof Panel.





TOOLS AND HARDWARE REQUIRED FOR THIS PAGE




SEC 8



SEC

8.3


The bottom lip of the Roof Panel fits over the Wall Panel. The tops of the Corner Wall Panels fit into the groove near the bottom of the Roof Panel. After aligning the holes in the Roof Panel with those in the Corner Wall Panels and Gables, secure the Roof Panel to the shed using the required hardware at the locations shown. **Repeat these steps for the second Roof Panel.**



Interior Upward View



TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



SEC 8



SEC


8.4

ROOF CAP INSTALLATION

Starting at the front side of your shed, attach the **Front Roof Cap (AGG)** to the Roof Panels and Entry Gable and then attach the **Rear Roof Cap (AFW)** to the Roof Panels and Rear Gable.



Note: Use only a hand screwdriver for this step.




CAUTION

Only hand tighten screws. Do not overtighten. Overtightening may damage plastic parts and void warranty.

SEC

8.5



Connect the Roof Caps to each other using two (2) **1/4" x 5/8" Pan-Head Screws (ADZ)**.






TOOLS AND HARDWARE REQUIRED FOR THIS PAGE


SEC 8



AXX (x2)
(Not to scale)



ADX (x6)



AED (x6)



SEC

8.6


SKYLIGHT INSTALLATION

Pre-fold **Skylight (AHC)** before installing. Push folded Skylight up through opening between the Roof Caps; open Skylight; use tabs to pull Skylight down into place. Fasten Skylight in place with six (6) **#10 x 1" Fender Washers (AED)** and six (6) **#10 x 1/2" Pan-Head Screws (ADX)** (pull down on tabs while inserting screws to provide resistance).



Note: Use only a hand screwdriver for this step.


AHC



AHC



Pull down on tabs while inserting screws.




SEC

8.7

GABLE CLIP INSERTION


Insert the **Truss Hole Inserts (AXX)** between the rear Gable and the rear Wall of the Shed as shown.



Note: Gable Clip can only be inserted with the arrow pointing up.



TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



SEC 8




NOTE: YOU NEED ONLY COMPLETE THIS STEP IF THIS SHED IS FOR A DISPLAY MODEL ONLY

SEC

8.8

TRUSS INSTALLATION


Push the Truss Assembly up against the Roof about 1" in from the Rear Gable as shown. Secure the Truss Assembly to the Roof using sixteen (16) #10" x 1/2" Pan-Head Screws (ADX).



SEC 9 SHELF INSTALLATION

HARDWARE REQUIRED



Hardware shown at actual size



ADZ (x46)
1/4" x 5/8" Pan-Head Screw
(Only 30 used)

METAL PARTS REQUIRED

Part shown at 8% of actual size



AFM (x2)
Shelf Support Channel

Part shown at 15% of actual size



AIY (x6)
Shelf Support Bracket

PLASTIC PARTS REQUIRED

Part shown at 4% of actual size




AFV (x1)
90" Shelf



1002314
AFS (x2)
10" x 30" Shelf

Part shown at 8% of actual size




AFZ (x2)
Corner Shelf

TOOLS REQUIRED





Phillips Screwdriver



Safety Glasses



TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



ADZ (x8)

SEC 9





SEC

WALL/SHELF SUPPORT CHANNEL INSTALLATION



9.1

Insert a **Shelf Support Channel (AFM)** into the slots in the Wall Panels directly below the Right Truss notch, and secure with four (4) **1/4" x 5/8" Pan-Head Screws (ADZ)**. Insert a second Shelf Support Channel in the slot directly to the right of the Left Truss Notch and secure with four (4) **1/4" x 5/8" Pan-Head Screws**.





TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



ADZ (x6)

SEC 9




SEC

90" SHELF INSTALLATION

9.2

Set a **Shelf Support Bracket (AIY)** into the slots of each of the Shelf Support Channels. The slots must be at the same height.




Note: Insert Shelf Support Bracket at an angle.


SEC

9.3

Fold up flaps on the end of **90" Shelf (AFV)**. Set Shelf on Brackets with indentations toward wall, and secure with six (6) **1/4" x 5/8" Phillips Pan-Head Screws (ADZ)**.



Upward view



WARNING



The weight limit for a 90" Shelf is 30 lb. per 30" section of Wall Panel. Failure to heed this warning could result in property damage and/or personal injury.



Note: There are only holes for screws along front side of the Shelf (front is labeled "Front" on underside of Shelf).



TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



ADZ (x8)

SEC 9





SEC

10" x 30" SHELF INSTALLATION

9.4

Insert a pair of **10" Shelf Support Brackets (AIY)** into the slots in the Wall/Shelf Support Channels and set a **10" x 30" Shelf (AFS)** on Brackets. Secure with four (4) **1/4" X 5/8" Phillips Pan-Head Screws (ADZ)**. Repeat this step for the second 10" x 30" Shelf.





WARNING

The total weight placed on a 10" x 30" Shelf cannot exceed 30 pounds (14kg.) per Wall Panel.



TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



ADZ (x8)

SEC. 9




SEC


9.4

CORNER SHELF INSTALLATION


Fold up edges of a **Corner Shelf (AFZ)**. Line-up holes in the Corner Shelf with a set of pre-made holes in any Corner Panel as shown. Secure with four (4) **1/4" x 5/8" Phillips Pan-Head Screws (ADZ)**. Repeat this step for the second **Corner Shelf**.



Holes



ADZ




WARNING

The total weight placed on a Corner Shelf cannot exceed 10 lb. (4.5 kg).

SEC 10 PEGBOARD STRIP INSTALLATION


HARDWARE REQUIRED

Hardware shown at actual size




ADW (x10)
#10" x 3/4" Pan-Head Screw


Hardware shown at 50% of actual size




AIG (x1)
4" Double-Arm Hook




AIJ (x2)
Toolholder



AIF (x1)
2" Double-Arm Hook



AIH (x3)
J-Hook




AII (x3)
L-Hook

METAL PARTS REQUIRED

NO METAL PARTS REQUIRED FOR THIS SECTION

PLASTIC PARTS REQUIRED

Parts shown at 15% of actual size



AFU (x2)
Pegboard Strip

TOOLS REQUIRED



Phillips Screwdriver





Safety Glasses



Level



TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



ADW (x10)

SEC 10




SEC

PEGBOARD STRIP INSTALLATION

10.1

Using a level, position the **Pegboard Strip (AFU)** in any desired location along a Wall Panel wall. Screw the Pegboard Strip to the Wall using five (5) **#10 x 3/4" Phillips Pan-Head Screws (ADW)**. See Note. Repeat this step for second Pegboard Strip.

! Note: The Pegboard Strip is screwed directly into the plastic. Line up the Strip anywhere on Wall so holes are over plastic (and not over a groove in the Wall).



! Note: Ensure the Pegboard Strip is level before inserting Screws.

SEC


10.2

Insert Hooks (AIF, AIG, AIH, AII, and AIJ).

SEC 11 FINAL STEPS

HARDWARE REQUIRED

Hardware shown at actual size




ADZ (x3)
1/4" x 5/8" Pan-Head Screw
(Only 2 used)

METAL PARTS REQUIRED

NO METAL PARTS REQUIRED FOR THIS SECTION

PLASTIC PARTS REQUIRED

Part not shown to any particular scale




AYJ (x1)
Battery Powered Light

TOOLS REQUIRED




Phillips Screwdriver



Rubber Mallet



Level





Safety Glasses



AIX (x4)
Wood Shim (Provided)



TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



ADZ (x2)

SEC 11



SEC




11.1

BATTERY POWERED LIGHT INSTALLATION

Open the battery compartment and remove the plastic cap between the battery and the metal contact. The **Battery Powered Light (AYJ)** can be installed above the Right Corner Shelf (on 8' Sheds) or on the Front Gable. Insert two (2) **1/4" X 5/8" Pan-Head Screws (ADZ)** half-way into the pilot holes on the Corner Wall Panel or Front Gable. Hang Light on Screws. Gently tap the light to turn it on or off.


Battery Light Features:

- Adjustable Timer
- Auto shutoff
- Battery powered
- Easy on/off
- Easy mounting





TOOLS AND HARDWARE REQUIRED FOR THIS PAGE



AIX (x4)
Wood Shim

NO HARDWARE PROVIDED FOR THIS STEP

SEC 11



SEC

11.2

DOOR ALIGNMENT

In some cases, the shed doors may not completely line up at the tops (fig. 1). When this happens, identify which side is higher and use a **Wooden Shim (AIX)** to slightly raise the back corner of the high side until doors line up (fig. 2). If doors need further adjustment, insert another shim under the front corner opposite of the first shim. If the doors still need further adjustment, stack additional shims (one at a time) alternating between the back and front shims. After doors are aligned, cut off any portion of wood shim that is still exposed. From inside the shed, drive a 1" nail through the floor into the shim to hold it in place. **Tighten all anchoring hardware now.**




Fig. 1





Fig. 2



Note: Shim should be placed at the corner, running directly under one wall.

CLEANING & CARE

Congratulations on your Lifetime® Outdoor Shed purchase. By following the instructions below, your new Lifetime shed should provide you with years of service and enjoyment.

Cleaning and Care

The polyethylene walls and shelves are stain- and solvent resistant. Most stains can be removed, using a mild soap and a soft-bristled brush. Abrasive cleaning materials may scratch the plastic and are not recommended. Repair scratches or rust spots on the metal by sanding the affected area lightly; using a rust preventative spray primer; and finally, spraying with a high-gloss spray enamel paint. Avoid placing a direct heat source on or near surfaces unless using a heat barrier.

LIFETIME OUTDOOR SHED EQUIPMENT

10-YEAR LIMITED FACTORY WARRANTY

THE MANUFACTURER RESERVES THE RIGHT TO MAKE SUBSTITUTIONS TO WARRANTY CLAIMS IF PARTS ARE UNAVAILABLE OR OBSOLETE.

1. Lifetime outdoor sheds are warranted to the original purchaser to be free from defects in material or workmanship for a period of ten years from the date of original retail purchase. The word "defects" is defined as imperfections that impair the use of the product. Defects resulting from misuse, abuse or negligence will void this warranty. This warranty does not cover defects due to improper installation, alteration or accident. This warranty does not cover damage caused by vandalism, rusting, "acts of nature" or any other event beyond the control of the manufacturer.
2. This warranty is nontransferable and is expressly limited to the repair or replacement of defective product. If the product is defective within the terms of this warranty, Lifetime Products, Inc. will repair or replace defective parts at no cost to the purchaser. Shipping charges to and from the factory are not covered and are the responsibility of the purchaser. Labor charges and related expenses for removal, installation or replacement of the shed or its components are not covered under this warranty.
3. This warranty does not cover scratching or scuffing of the product that may result from normal usage. In addition, defects resulting from intentional damage, negligence, unreasonable use or hanging from the truss will void this warranty.
4. Liability for incidental or consequential damages is excluded to the extent permitted by law. While every attempt is made to embody the highest degree of safety in all equipment, freedom from injury cannot be guaranteed. The user assumes all risk of injury resulting from the use of this product. All merchandise is sold on this condition, and no representative of the company may waive or change this policy.
5. This product is not intended for institutional or commercial use; Lifetime Products, Inc. does not assume any liability for such use. Institutional or commercial use will void the warranty.
6. This warranty is expressly in lieu of all other warranties, expressed or implied, including warranties of merchantability or fitness for use to extent permitted by Federal and state law. Neither Lifetime Products, Inc., nor any representative assumes any other liability in connection with this product. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

ALL WARRANTY CLAIMS MUST BE ACCOMPANIED BY A SALES RECEIPT.

REPORT PRODUCT DEFECTS IN WRITING TO:

Lifetime Products, Inc., PO Box 160010 Clearfield, UT 84016-0010
or call (800) 225-3865 M-F 7 a.m. to 5 p.m. MST.

Please include your dated sales receipt and photographs of damaged parts.

To register the product, visit our Web site at www.lifetime.com



www.lifetime.com

©2004 Lifetime Products, Inc.

PO Box 160010 • Freeport Center, Bldg. D-11 Clearfield, Utah 84016-0010
T: 800-225-3865 • F: 801-728-1907

ENHANCE YOUR LIFETIME® PURCHASE BY ADDING ACCESSORIES OR OTHER GREAT PRODUCTS

To purchase accessories or other Lifetime Products, visit us at:

www.lifetime.com

Or call: 1-800-424-3865

